ACOUSTO-ULTRASONIC NONDESTRUCTIVE EVALUATION OF MATERIALS USING LASER BEAM GENERATION AND DETECTION

Robert D. Huber and Robert E. Green Jr.
Center for Nondestructive Evaluation
The Johns Hopkins University
and
Alex Vary and Harold Kautz
NASA/Lewis Research Center

This work has been supported in part by NASA/Lewis Research Center Through NASA Grant #NAG3-728

RESEARCH OBJECTIVE

TO INVESTIGATE THE POSSIBILITY OF USING LASER GENERATION AND DETECTION OF ULTRASOUND TO REPLACE PIEZOELECTRIC TRANSDUCERS FOR THE ACOUSTO-ULTRASONIC TECHNIQUE.

ADVANTAGES OF LASER ACOUSTO-ULTRASONICS

- NON-CONTACT TESTING
- PIEZOELECTRIC TRANSDUCER COUPLING PROBLEMS ELIMINATED

CONTACT PRESSURE

COUPLANT

TESTING HOT SURFACES OR IN HOSTILE ENVIRONMENTS


- RESONANCE OF TRANSDUCERS ELIMINATED
- POINT DETECTION
- NARROW AND WIDE BAND DETECTION
- DETECTION NEAR MATERIAL EDGES

DISADVANTAGES OF LASER DETECTION


- SURFACE MUST BE REFLECTIVE
- NOT AS SENSITIVE AS PIEZOELECTRIC TRANSDUCERS
- OPTICAL SYSTEMS ARE OFTEN MORE EXPENSIVE

TYPES OF INTERFEROMETERS USED

- PATH STABILIZED BULK SYSTEM
- HETERODYNE FIBER OPTIC SYSTEM



PATH STABILIZED INTERFEROMETER



HETERODYNE FIBER OPTIC INTERFEROMETER

INTERFEROMETER SENSITIVITY CONSIDERATIONS

h: PLANCK'S CONSTANT

λ: OPTICAL WAVELENGTH


 η : DETECTOR QUANTUM EFFICIENCY


 δ : SIGNAL AMPLITUDE

 Δv : DETECTION BANDWIDTH


R : SAMPLE REFLECTIVITY

Po: LASER POWER






SECONDS




LASER GENERATION OF ULTRASOUND


17 mJ PER PULSE
4 ns PULSE LENGTH
3 mm BEAM DIAMETER




NON-CONTACT GENERATION AND DETECTION OF ULTRASOUND IN AN ALUMINUM BLOCK


Theoretical Surface Displacement For Laser Generated Ultrasound In A 1.5 in Al Block On Epicenter







Theoretical Surface Displacement For Laser Generated Ultrasound In A 1.5 in Al Block 7/8 in Off Epicenter









NON-CONTACT GENERATION AND DETECTION OF ULTRASOUND IN A BRASS PLATE












Figure 2. THEORETICAL RECORD OF A STEP-LOADING POINT SOURCE STRIKING AN INFINITE HALF-SPACE




ORIGINAL PAGE IS OF POOR QUALITY

DIMENSIONS OF SAMPLES USED IN LASER ACOUSTO-ULTRASONIC TESTS





(ALL SPECIMENS 0.5 INCHES WIDE)


*3M SILVER POLYESTER FILM TAPE WAS USED AT DETECTION SITES TO INCREASE REFLECTIVITY





LASER ACOUSTO-ULTRASONICS













SUMMARY


LASER ACOUSTO-ULTRASONICS COMPLEMENTS
STANDARD PIEZOELECTRIC ACOUSTO-ULTRASONICS
AND OFFERS NON-CONTACT NONDESTRUCTIVE
EVALUATION.



ORIGINAL PAGE BLACK AND WHITE PHOTOGRAPH



ORIGINAL PAGE
BLACK AND WHITE PHOTOGRAPH



ORIGINAL PAGE BLACK AND WHITE PHOTOGRAPH 82

ORIGINAL PAGE IS OF POOR QUALITY